

RIDEMAX FL 693 M

TIRE SIZE	750/60 R 30.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	181 D



РАЗМЕРЫ IS STANDARD

SW (MM)	754	RIM REC	AG 24.00
OD (MM)	1675	ECE	E4-106R-001499
SLR (MM)	728	SRI	800
RC (MM)	5092		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2780	3155	3835	4435	5110	5785	6235	6910	7510
65	3055	3465	4210	4870	5610	6355	6850	7590	8250
50	3700	4195	5095	5895	6790	7690	8290	9190	9985
40	4155	4715	5725	6620	7630	8640	9315	10325	11220
25	4825	5475	6650	7695	8865	10040	10820	11995	13035
10	5500	6240	7575	8765	10100	11435	12330	13665	14850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.