


# EARTHMAX SR 22



<b>TIRE SIZE</b>	<b>20.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VÄGHYVLARE / HJULLASTARE / BULLDOZER / HJULLASTARE / BULLDOZER / VÄGHYVLARE
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	161 A8 ; 186 A2

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94040803	<b>RIM REC</b>	17.00/2.0
<b>OD (IN)</b>	58.7	<b>RIM ALT</b>	17.00/1.7
<b>SLR (IN)</b>	25.2	<b>TRA CODE</b>	G2/L2
<b>RC (IN)</b>	169.9	<b>STAR RATING</b>	★

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73
25	5360	6150	6950	7600	8550	9100	9650	10200	-	-	-	-	-
5	-	-	-	-	-	-	-	-	17600	18200	19300	19800	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.