

# FLOTATION 648

<b>TIRE SIZE</b>	<b>700/50 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	156 A8/153 B
<b>LI/SS FREE ROLLING</b>	168 A8/164 B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	700	<b>RIM REC</b>	24.00
<b>OD (MM)</b>	1270	<b>ECE</b>	E4-106R-002270
<b>SLR (MM)</b>	550	<b>PR</b>	12
<b>RC (MM)</b>	3775		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.60	1.80
10 FR	7050	7315	7840
20 FR	6345	6585	7055
30 FR	5640	5850	6270
40 FR	5035	5225	5600
50 FR	4530	4705	5000
10 DW	5035	5230	5600
20 DW	4530	4705	5040
30 DW	4025	4185	4480
40 DW	3595	3735	4000
50 DW	3235	3360	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.