DATA SHEET

PRINTED ON
23-04-2026

PORTMAX PM 93 PLUS

TYRE SIZE	**450/95 R 25**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	STRADDLE CARRIER
VERSION	INDUSTRIAL
TYRE TYPE	TL
LI/SS	204 A5

DIMENSIONS IS STANDARD

OD (MM)	1515	**RIM ALT**	13.00/2.0
SLR (MM)	699	**STAR RATING**	★★
RC (MM)	4582		
RIM REC	11.25/2.0		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	10
25	16000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..