

# PL 801

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 7.00 - 15  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊗ BIAS   |
| <b>MACHINERY</b>    | ROTTERANDE HARV / SKÖRDEMASKIN /<br>GAFFELTRUCK / SKÖRDEMASKIN /<br>ARBETSFORDON / GAFFELTRUCK |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSIONER US STANDARD

|                 |          |                |             |
|-----------------|----------|----------------|-------------|
| <b>USA CODE</b> | 94007233 | <b>RIM ALT</b> | 4.33 R; 5.0 |
| <b>SW (IN)</b>  | 7.9      | <b>PR</b>      | 12          |
| <b>OD (IN)</b>  | 29.5     |                |             |
| <b>RIM REC</b>  | 5.5      |                |             |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b>          | <b>120</b> |
|---------------------------|------------|
| <b>15 LOAD WHEEL</b>      | 6770       |
| <b>15 STEER WHEEL</b>     | 5205       |
| <b>5 OTHER VEHICLES</b>   | 6770       |
| <b>15 OTHER VEHICLES</b>  | 5205       |
| <b>STATIC SIDE LOADER</b> | 7860       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.