DATA SHEET

Neuestes Update
2-06-2026

AS 504

TIRE SIZE	**10.0/75 -15.3**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	123 A8
LI/SS FREE ROLLING	135 A8

ABMESSUNGEN US STANDARD

USA-CODE	94027422	**RC (IN)**	94.6
SW (IN)	10.4	**RIM REC**	9.00
OD (IN)	30.9	**ECE**	E4-106R-001823
SLR (IN)	14.2	**PR**	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	103
5 FR	6720
15 FR	5720
20 FR	5380
25 FR	4810
5 DW	4780
15 DW	4070
20 DW	3820
25 DW	3420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..