

FLOTATION 648

TIRE SIZE	600/55 - 26.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	159 A8/156 B
LI/SS FREE ROLLING	170 A8/167 B



ABMESSUNGEN US STANDARD

USA-CODE	94006441	RC (IN)	158.1
SW (IN)	24.1	RIM REC	AG 20.00
OD (IN)	53.3	ECE	E4-106R-002276
SLR (IN)	22.9	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	32	35	38
5 FR	16790	17670	18520
10 FR	15110	15910	16670
20 FR	13440	14130	14810
25 FR	11990	12620	13230
30 FR	10790	11360	12010
5 DW	12260	12890	13500
10 DW	11020	11600	12160
20 DW	9800	10310	10800
25 DW	8750	9200	9640
30 DW	7880	8290	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.