


# AW 711

<b>TIRE SIZE</b>	<b>VF 410/50 R 16.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	153 B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94055814	<b>RC (IN)</b>	98.9
<b>SW (IN)</b>	16.1	<b>RIM REC</b>	AG 13.00
<b>OD (IN)</b>	32.9	<b>ECE</b>	E11-106R-005024
<b>SLR (IN)</b>	13.8		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	67
<b>FROM 5 TO 30 MPH</b>	2260	2970	3590	4170	4790	5430	5850	6420	7040	8050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.