


FL 630 ULTRA

TYRE SIZE	500/60 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRAILER / IMPLEMENTS
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	155 D ; 166 A8



DIMENSIONS IS STANDARD

SW (MM)	503	RIM REC	AG 16.00
OD (MM)	1172	RIM ALT	15.00; 16.00; 17.00
SLR (MM)	521	ECE	E4-106R-001404
RC (MM)	3592	SRI	550

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1130	1310	1485	1780	2085	2385	2670	2970	3250	3530
65	1240	1435	1630	1950	2290	2610	2930	3255	3565	3875
50	1505	1740	1970	2345	2770	3160	3540	3940	4315	4690
40	1700	1965	2230	2680	3110	3560	3990	4440	4880	5300
25	1960	2270	2575	3080	3615	4110	4630	5130	5635	6125
10	2235	2585	2930	3500	4100	4700	5250	5850	6420	6975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.