


FL 630 ULTRA

600/55 R 26.5

| | |
|---------------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | YAYICI / TANKER / RÖMORK / UYGULAMALI MAKINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 165 D ; 176 A8 |



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 611 | RIM REC | AG 20.00 |
| OD (MM) | 1333 | ECE | E11-106R-006813 |
| SLR (MM) | 579 | SRI | 625 |
| RC (MM) | 4070 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 65 | 1650 | 1910 | 2165 | 2630 | 3040 | 3505 | 3970 | 4275 | 4740 | 5150 |
| 50 | 2000 | 2310 | 2620 | 3180 | 3680 | 4240 | 4805 | 5180 | 5740 | 6235 |
| 40 | 2275 | 2630 | 2985 | 3625 | 4190 | 4830 | 5470 | 5895 | 6535 | 7100 |
| 25 | 2605 | 3015 | 3420 | 4155 | 4805 | 5540 | 6270 | 6760 | 7490 | 8140 |
| 10 | 2970 | 3435 | 3895 | 4730 | 5470 | 6305 | 7140 | 7695 | 8530 | 9270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.