DATA SHEET

PRINTED ON
21-04-2026

FLOTATION 648

TIRE SIZE	**350/65 - 22.5**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	139 A8/135 B
LI/SS FREE ROLLING	151 A8/147 B

DIMENSIONS IS STANDARD

SW (MM)	358	**RIM REC**	AG 11.75
OD (MM)	1030	**ECE**	E11-106R-004551
SLR (MM)	451	**PR**	18
RC (MM)	3069		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.00	3.00	4.00	5.00
10 FR	2830	3585	4240	4830
20 FR	2545	3225	3820	4345
30 FR	2260	2865	3395	3865
40 FR	2020	2560	3030	3450
50 FR	1820	2305	2725	3075
10 DW	1990	2520	2990	3400
20 DW	1790	2270	2690	3060
30 DW	1590	2015	2390	2720
40 DW	1420	1800	2135	2430
50 DW	1280	1620	1920	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..