

# AS 504

<b>TIRE SIZE</b>	<b>15.5/80 - 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	148 A8
<b>LI/SS FREE ROLLING</b>	160 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94019458	<b>RC (IN)</b>	152.6
<b>SW (IN)</b>	15.1	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	49.7	<b>RIM ALT</b>	W 13; W 14 L
<b>SLR (IN)</b>	22.4	<b>ECE</b>	E11-106R-004614

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	51
5 FR	13890
15 FR	11810
20 FR	11110
25 FR	9920
5 DW	9720
15 DW	8270
20 DW	7780
25 DW	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.