

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 380/70 R 20 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 132 A8/B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|---------------|
| CÓDIGO USA | 94021987 | RC (IN) | 126.5 |
| SW (IN) | 15.0 | RIM REC | W 12 |
| OD (IN) | 42.6 | RIM ALT | W 11; W 13 |
| SLR (IN) | 19.0 | ECE | E4-106R-00648 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 30 | 2070 | 2380 | 2730 | 3090 | 3440 | 3790 | 4100 | 4400 |
| 25 | 2070 | 2380 | 2730 | 3090 | 3440 | 3790 | 4100 | 4400 |
| 20 | 2230 | 2560 | 2930 | 3310 | 3680 | 4070 | 4400 | 4720 |
| 5 LT | 2780 | 3200 | 3670 | 4140 | 4620 | 5080 | 5500 | 5910 |
| 5 HT | 2230 | 2560 | 2930 | 3310 | 3680 | 4070 | 4400 | 4720 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.