

# ROCK GRIP IND4 (ECH)

|                     |                                    |
|---------------------|------------------------------------|
| <b>TIRE SIZE</b>    | 12.00 - 24                         |
| <b>UM</b>           | IS STANDARD                        |
| <b>CONSTRUCTION</b> | ❖ BIAS                             |
| <b>MACHINERY</b>    | MANIPULATOR DE CONTAINERE<br>GOALE |
| <b>VERSION</b>      | PORT INDUSTRIAL                    |
| <b>TIRE TYPE</b>    | TT                                 |



## DIMENSIUNI IS STANDARD

|                 |      |                 |      |
|-----------------|------|-----------------|------|
| <b>OD (MM)</b>  | 1265 | <b>RIM ALT</b>  | 8.0  |
| <b>SLR (MM)</b> | 595  | <b>PR</b>       | 24   |
| <b>RC (MM)</b>  | 3755 | <b>TRA CODE</b> | IND4 |
| <b>RIM REC</b>  | 8.5  |                 |      |

## LOAD CAPACITY (KG/TIRE)

|                   |              |
|-------------------|--------------|
| <b>KM/H / BAR</b> | <b>10.00</b> |
| 10                | 10270        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.