


EARTHMAX SR 22

| | |
|---------------------|--|
| TIRE SIZE | 14.00 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | NIVELEUSE / CHARGEUR / BULLDOZER / CHARGEUR / BULLDOZER / NIVELEUSE |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 153 A8 ; 175 A2 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|--------------------|-------------------|
| CODE USA | 94048816 | RIM REC | 8.00 TG |
| OD (IN) | 53.9 | RIM ALT | 9.00 GR; 10.00 VA |
| SLR (IN) | 24.6 | TRA CODE | G2/L2 |
| RC (IN) | 163.0 | STAR RATING | ★ |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 29 | 33 | 36 | 40 | 44 | 47 | 51 | 54 | 76 | 80 |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 25 | 4940 | 5360 | 5840 | 6150 | 6600 | 7150 | 7400 | 8050 | - | - |
| 5 | - | - | - | - | - | - | - | - | 14800 | 15200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.