


AGRIMAX FORCE

TIRE SIZE	IF 650/65 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	169 D



DIMENSIONER IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1830	ECE	E11-106R-005103
SLR (MM)	830	SRI	875
RC (MM)	5510	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2475	2900	3320	3690	4060	4375	4900	5275
FROM 65 TO 40	2725	3190	3650	4060	4465	4810	5390	5800
30	2830	3315	3795	4220	4640	5000	5605	6030
20	2940	3445	3940	4380	4820	5190	5820	6260
10	3460	4050	4635	5155	5670	6105	6845	7365
UPTO 30 CYC	3540	4145	4745	5275	5800	6250	7005	7540
UPTO 15 CYC	4220	4940	5655	6290	6920	7455	8350	8990
UPTO 10 CYC	4630	5420	6025	6900	7590	8175	9160	9860
10HT	2830	3315	3795	4220	4640	5000	5605	6030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.