


# FL 639

<b>TIRE SIZE</b>	<b>710/40 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRIDARE / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 B ; 158 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94063246	<b>RC (IN)</b>	137.5
<b>SW (IN)</b>	28.6	<b>RIM REC</b>	AG 24.00
<b>OD (IN)</b>	44.9	<b>ECE</b>	E11-106R-006479
<b>SLR (IN)</b>	19.8		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	20	23	26	29	32	35	38	41	44	46
<b>30 FR</b>	5080	5840	6600	7325	8050	8700	9350	10025	10700	11500	12300	12750	13200
<b>30 DW</b>	3640	4160	4680	5180	5680	6140	6600	7100	7600	8200	8800	9075	9350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.