


# RIDEMAX FL 693 M



|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>560/60 R 22.5</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS   |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 165 D ; 162 E  |

## DIMENSIONS IS STANDARD

|                 |      |                |                        |
|-----------------|------|----------------|------------------------|
| <b>SW (MM)</b>  | 543  | <b>RIM REC</b> | AG 16.00               |
| <b>OD (MM)</b>  | 1244 | <b>RIM ALT</b> | 16.00; 17.00; AG 20.00 |
| <b>SLR (MM)</b> | 552  | <b>ECE</b>     | E4-106R-001403         |
| <b>RC (MM)</b>  | 3767 | <b>SRI</b>     | 600                    |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 5.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70         | 1555 | 1745 | 2170 | 2465 | 2850 | 3230 | 3530 | 3870 | 4250 | 4750 |
| 65         | 1690 | 1900 | 2360 | 2685 | 3100 | 3515 | 3840 | 4210 | 4625 | 5150 |
| 50         | 2050 | 2300 | 2860 | 3250 | 3755 | 4260 | 4650 | 5100 | 5600 | 6235 |
| 40         | 2300 | 2580 | 3210 | 3650 | 4215 | 4785 | 5225 | 5725 | 6290 | 7005 |
| 25         | 2670 | 3000 | 3730 | 4240 | 4900 | 5560 | 6070 | 6655 | 7310 | 8140 |
| 10         | 3040 | 3415 | 4250 | 4830 | 5580 | 6330 | 6910 | 7580 | 8325 | 9270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.