


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 15.0/55 - 17 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 128 A8 |
| LI/SS FREE ROLLING | 141 A8 |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94018895 | RC (IN) | 102.7 |
| SW (IN) | 15.0 | RIM REC | 13.00 |
| OD (IN) | 35.0 | RIM ALT | 13 |
| SLR (IN) | 15.6 | ECE | E4-106R-001572 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 52 |
|-----------|------|
| 5 FR | 7950 |
| 15 FR | 6760 |
| 20 FR | 6360 |
| 25 FR | 5680 |
| 5 DW | 5560 |
| 15 DW | 4720 |
| 20 DW | 4430 |
| 25 DW | 3970 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.