


# AGRIMAX RT 600

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>1050/50 R 32</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / TRACTOR / MAȘINI DE IMPLEMENTARE            |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 184 A8 ; 181 B   |



## DIMENSIUNI IS STANDARD

|                 |      |                |                      |
|-----------------|------|----------------|----------------------|
| <b>SW (MM)</b>  | 1059 | <b>RIM REC</b> | 36.0 VA (multipiece) |
| <b>OD (MM)</b>  | 1863 | <b>ECE</b>     | E4-106R-000813       |
| <b>SLR (MM)</b> | 826  | <b>SRI</b>     | 875                  |
| <b>RC (MM)</b>  | 5700 |                |                      |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.0  | 1.4  | 1.6  | 2.0   | 2.4   | 2.8   | 3.2   | 3.4   | 3.8   |
|------------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 50         | 3715 | 4210 | 5280 | 5860 | 6520  | 7015  | 7675  | 8250  | -     | -     |
| 40         | 4050 | 4590 | 5760 | 6390 | 7110  | 7650  | 8370  | 9000  | -     | -     |
| 30         | 4335 | 4915 | 6165 | 6840 | 7610  | 8190  | 8960  | 9630  | -     | -     |
| 10 LT      | 5430 | 6155 | 7720 | 8565 | 9530  | 10255 | 11220 | 12060 | -     | -     |
| 10 HT      | 4335 | 4915 | 6165 | 6840 | 7610  | 8190  | 8960  | 9630  | -     | -     |
| 10 CYC     | -    | 6810 | 8725 | 9565 | 11095 | 11555 | 12645 | 13595 | 14195 | 15300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.