


# FL 630 SUPER

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>750/45 R 26.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPREADER / TANKER / TRAILER /<br>IMPLEMENTS  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 170 D  |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94046096 | <b>RC (IN)</b> | 163.3          |
| <b>SW (IN)</b>  | 29.7     | <b>RIM REC</b> | AG 24.00       |
| <b>OD (IN)</b>  | 53.1     | <b>ECE</b>     | E4-106R-001652 |
| <b>SLR (IN)</b> | 23.9     |                |                |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 15   | 17    | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 3860 | 4400 | 4940  | 6140  | 6990  | 8070  | 9150  | 10000 | 10940 | 12040 |
| 40        | 4230 | 4830 | 5420  | 6750  | 7670  | 8860  | 10050 | 10980 | 12040 | 13230 |
| 30        | 5130 | 5850 | 6570  | 8170  | 9290  | 10720 | 12170 | 13290 | 14570 | 16000 |
| 25        | 5760 | 6580 | 7390  | 9180  | 10440 | 12060 | 13680 | 14940 | 16380 | 17990 |
| 15        | 6690 | 8580 | 10660 | 12120 | 14010 | 14010 | 15880 | 17350 | 19020 | 20900 |
| 5         | 7630 | 8700 | 9770  | 12150 | 13810 | 15960 | 18100 | 19760 | 21670 | 23810 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.