

MAGLIFT



MAGLIFT
S O L I D T I R E S

MAGLIFT



MAGLIFT has been particularly designed for forklift in industrial and logistic operations. This solid tire features high load capacity and outstanding comfort. MAGLIFT shows excellent cut and chip resistance resulting in a long tire life. Its reinforced structure eliminates slippage risks whilst the special bead shape simplifies mounting operations on the rim.



	SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
						REC RIM	ALT RIM					
												
Ø8"	18X7 -8 (180/70 - 8)	94035540	-	-		4.33 R - 8	-		18.0	0	0	STD
	15X4.5 -8 (125/75 - 8)	94052028	-	-		3.00 D - 8	-		14.9	0	0	LIP - NM
	15X4.5 -8 (125/75 - 8)	94045129	-	-	-	3.00 D - 8	-		14.9	0	0	STD
	16X6 -8 (150/75 - 8)	94036950	-	-		4.33 R - 8	-		16.6	0	0	LIP
	5.00 - 8	94035526	-	-	-	3.00 D - 8	-		18.2	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
5.00 - 8	94036837	-	-	-	3.00 D - 8	-		18.2	0	0	LIP
5.00 - 8	94053421	-	-	-	3.00 D - 8	-		18.2	0	0	LIP - NM
15X4.5 - 8 (125/75 - 8)	94045334	-	-		3.00 D - 8	-		14.9	0	0	LIP
18X7 - 8 (180/70 - 8)	94053414	-	-		4.33 R - 8	-		18.0	0	0	LIP - NM
4.00 - 8	94036899	-	-	-	3.00 D - 8	-		16.0	0	0	LIP
16X6 - 8 (150/75 - 8)	94053438	-	-		4.33 R - 8	-		16.6	0	0	LIP - NM
4.00 - 8	94054633	-	-	-	3.00 D - 8	-		16.0	0	0	LIP - NM
18X7 - 8 (180/70 - 8)	94036844	-	-		4.33 R - 8	-		18.0	0	0	LIP
5.00 - 8	94051540	-	-	-	3.00 D - 8	-		18.2	0	0	STD - NM
16X6 - 8 (150/75 - 8)	94036905	-	-		4.33 R - 8	-		16.6	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
16X6 -8 (150/75 - 8)	94051571	-	-		4.33 R - 8	-		16.6	0	0	STD - NM
4.00 - 8	94036608	-	-	-	3.00 D - 8	-		16.0	0	0	STD
4.00 - 8	94054497	-	-	-	3.00 D - 8	-		16.0	0	0	STD - NM
15X4.5 -8 (125/75 - 8)	94054541	-	-		3.00 D - 8	-		14.9	0	0	STD - NM
18X7 -8 (180/70 - 8)	94050437	-	-		4.33 R - 8	-		18.0	0	0	STD - NM
	6.00 - 9	94054640	-	-	-	4.00 E - 9	-	20.8	0	0	LIP - NM
	140/55 - 9	94054596	-	-	-	4.00 E - 9	-	14.8	0	0	STD - NM
	21X8 -9 (200/75 - 9)	94044542	-	-		6.00 E - 9	-	20.7	0	0	STD
	140/55 - 9	94044412	-	-	-	4.00 E - 9	-	14.8	0	0	STD
	21X8 -9 (200/75 - 9)	94054756	-	-		6.00 E - 9	-	20.7	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
140/55 - 9	94054787	-	-	-	4.00 E - 9	-		14.8	0	0	LIP - NM
21X8 - 9 (200/75 - 9)	94054558	-	-		6.00 E - 9	-		20.7	0	0	STD - NM
6.00 - 9	94036820	-	-	-	4.00 E - 9	-		20.8	0	0	LIP
21X8 - 9 (200/75 - 9)	94044559	-	-		6.00 E - 9	-		20.7	0	0	LIP
6.00 - 9	94052035	-	-	-	4.00 E - 9	-		20.8	0	0	STD - NM
140/55 - 9	94044429	-	-	-	4.00 E - 9	-		14.8	0	0	LIP
6.00 - 9	94036424	-	-	-	4.00 E - 9	-		20.8	0	0	STD
6.50 - 10	94054657	-	-	-	5.00 F - 10	-		22.6	0	0	LIP - NM
6.50 - 10	94036448	-	-	-	5.00 F - 10	-		22.6	0	0	STD
200/50 - 10	94054794	-	-	-	6.50 F - 10	-		18.0	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US - 01/08/2026

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
200/50 - 10	94044528	-	-	-	6.50 F - 10	-		18.0	0	0	STD
180/60 - 10	94063932	-	-	-	5.00F-10	-		18.1	0	0	LIP
200/50 - 10	94044535	-	-	-	6.50 F - 10	-		18.0	0	0	LIP
180/60 - 10	94063925	-	-	-	5.00F-10	-		18.1	0	0	STD
200/50 - 10	94054602	-	-	-	6.50 F - 10	-		18.0	0	0	STD - NM
6.50 - 10	94036868	-	-	-	5.00 F - 10	-		22.6	0	0	LIP
23X9 -10 (225/75 - 10)	94054565	-	-		6.50 F - 10	-		23.0	0	0	STD - NM
23X9 -10 (225/75 - 10)	94052042	-	-		6.50 F - 10	-		23.0	0	0	LIP - NM
23X9 -10 (225/75 - 10)	94044511	-	-		6.50 F - 10	-		23.0	0	0	LIP
23X9 -10 (225/75 - 10)	94044504	-	-		6.50 F - 10	-		23.0	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026

	SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
						REC RIM	ALT RIM					
												
	6.50 - 10	94051557	-	-	-	5.00 F - 10	-		22.6	0	0	STD - NM
Ø12"	7.00 - 12	94036875	-	-	-	5.00 S - 12	-		25.9	0	0	LIP
	27X10 - 12 (250/75 - 12)	94054770	-	-		8.00 G - 12	-		26.7	0	0	LIP - NM
	7.00 - 12	94035557	-	-	-	5.00 S - 12	-		25.9	0	0	STD
	27X10 - 12 (250/75 - 12)	94044917	-	-		8.00 G - 12	-		26.7	0	0	LIP
	315/45 - 12	94064083	-	-	-	10.00G-12	-		22.8	0	0	STD
	27X10 - 12 (250/75 - 12)	94044900	-	-		8.00 G - 12	-		26.7	0	0	STD
	315/45 - 12	94064090	-	-	-	10.00G-12	-		22.8	0	0	LIP
	23X10 - 12 (250/60 - 12)	94054763	-	-		8.00 G - 12	-		23.0	0	0	LIP - NM
	7.00 - 12	94054688	-	-	-	5.00 S - 12	-		25.9	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
23X10 -12 (250/60 - 12)	94050451	-	-		8.00 G - 12	-		23.0	0	0	LIP
7.00 - 12	94050000	-	-	-	5.00 S - 12	-		25.9	0	0	STD - NM
27X10 -12 (250/75 - 12)	94054589	-	-		8.00 G - 12	-		26.7	0	0	STD - NM
23X10 -12 (250/60 - 12)	94054572	-	-		8.00 G - 12	-		23.0	0	0	STD - NM
23X10 -12 (250/60 - 12)	94050017	-	-		8.00 G - 12	-		23.0	0	0	STD
Ø15"	300 - 15 (315/70 - 15)	-	-	-	8.0 - 15	-		32.3	0	0	LIP
	7.50 - 15	-	-	-	5.5 - 15	-		29.8	0	0	LIP
	7.00 - 15	-	-		5.5 - 15	-		28.7	0	0	LIP
	7.50 - 15	-	-	-	5.5 - 15	-		29.8	0	0	STD - NM
	300 - 15 (315/70 - 15)	-	-	-	8.0 - 15	-		32.3	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
7.00 - 15	94043958	-	-		5.5 - 15	-		28.7	0	0	STD
7.50 - 15	94054725	-	-	-	6.0 - 15	-		29.8	0	0	LIP - NM
28X12.5 - 15 (355/45 - 15)	94051359	-	-		9.75 - 15	-		27.0	0	0	STD
28X12.5 - 15 (355/45 - 15)	94061884	-	-		9.75 - 15	-		27.0	0	0	STD - NM
300 - 15 (315/70 - 15)	94054626	-	-	-	8.0 - 15	-		32.3	0	0	STD - NM
7.50 - 15	94044443	-	-	-	6.0 - 15	-		29.8	0	0	LIP
250 - 15 (250/70 - 15)	94054800	-	-	-	7.0 - 15	-		28.3	0	0	LIP - NM
250 - 15 (250/70 - 15)	94036936	-	-	-	7.0 - 15	-		28.3	0	0	LIP
8.25 - 15	94036912	-	-	-	6.5 - 15	-		32.2	0	0	LIP
8.25 - 15	94035571	-	-	-	6.5 - 15	-		32.2	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
32X12.5 -15 (355 / 65 - 15)	94066667	-	-		9.75 - 15	-		32.5	0	0	LIP
8.15 - 15 (28X9-15; 225/75-15)	94051564	-	-		7.0 - 15	-		27.2	0	0	STD - NM
250 - 15 (250/70 - 15)	94054619	-	-	-	7.0 - 15	-		28.3	0	0	STD - NM
7.50 - 15	94044610	-	-	-	5.5 - 15	-		29.8	0	0	STD
5.50 - 15	94069811	-	-	-	4.50 E - 15	-		26.2	0	0	STD
28X12.5 -15 (355/45 - 15)	94052448	-	-		9.75 - 15	-		27.0	0	0	LIP
8.15 - 15 (28X9-15; 225/75-15)	94036943	-	-		7.0 - 15	-		27.2	0	0	LIP
28X12.5 -15 (355/45 - 15)	94061891	-	-		9.75 - 15	-		27.0	0	0	LIP - NM
300 - 15 (315/70 - 15)	94036813	-	-	-	8.0 - 15	-		32.3	0	0	STD
8.15 - 15 (28X9-15; 225/75-15)	94054732	-	-		7.0 - 15	-		27.2	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
7.50 - 15	94054527	-	-	-	6.0 - 15	-		29.8	0	0	STD - NM
7.00 - 15	94054503	-	-		5.5 - 15	-		28.7	0	0	STD - NM
8.25 - 15	94054749	-	-	-	6.5 - 15	-		32.2	0	0	LIP - NM
32X12.5 - 15 (355 / 65 - 15)	94066650	-	-		9.75 - 15	-		32.5	0	0	STD
8.15 - 15 (28X9-15; 225/75-15)	94036547	-	-		7.0 - 15	-		27.2	0	0	STD
7.00 - 15	94054695	-	-		5.5 - 15	-		28.7	0	0	LIP - NM
7.50 - 15	94054701	-	-	-	5.5 - 15	-		29.8	0	0	LIP - NM
7.50 - 15	94044436	-	-	-	6.0 - 15	-		29.8	0	0	STD
8.25 - 15	94054534	-	-	-	6.5 - 15	-		32.2	0	0	STD - NM
250 - 15 (250/70 - 15)	94035564	-	-	-	7.0 - 15	-		28.3	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026

	SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
						REC RIM	ALT RIM					
												
NEW	355/50 - 15	94521845	-	-		9.75 - 15	-		28.4	0	0	STD
	355/50 - 15	94521852	-	-		9.75 - 15	-		28.4	0	0	LIP
	7.00 - 15		-	-		6.0 - 15	-		28.7	0	0	STD
Ø20"	12.00 - 20	94069583	-	-	-	8.50 - 20	-		42.9	0	0	STD
	10.00 - 20	94069514	-	-	-	7.50 - 20	-		40.7	0	0	STD
	10.00 - 20	94069774	-	-	-	8.00 - 20	-		40.7	0	0	STD
	10.00 - 20	94069767	-	-	-	7.00 - 20	-		40.7	0	0	STD
	11.00 - 20	94073818	-	-	-	8.00 - 20	-		41.7	0	0	STD
	9.00 - 20	94512485	-	-	-	7.00 - 20	-		39.0	0	0	STD
	12.00 - 20	94069552	-	-	-	8.00 - 20	-		42.9	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US - 01/08/2026

SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
9.00 - 20	94512010	-	-	-	6.50 - 20	-		39.0	0	0	STD
11.00 - 20	94074105	-	-	-	7.50 - 20	-		41.7	0	0	STD
	14.00 - 24	94073184	-	-	10.00 - 24	-		52.0	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026