

# FLOTATION 648

<b>TIRE SIZE</b>	<b>850/50 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	174 A8/170 B
<b>LI/SS FREE ROLLING</b>	186 A8/182 B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94006588	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	33.5	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	65.0	<b>ECE</b>	E4-106R-002284
<b>SLR (IN)</b>	28.0	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
<b>5 FR</b>	26080	27730	29320
<b>10 FR</b>	23470	24950	26390
<b>20 FR</b>	20870	22190	23460
<b>25 FR</b>	18630	19810	20940
<b>30 FR</b>	16770	17820	18740
<b>5 DW</b>	18400	19550	20680
<b>10 DW</b>	16560	17590	18610
<b>20 DW</b>	14720	15640	16540
<b>25 DW</b>	13140	13970	14770
<b>30 DW</b>	11830	12570	13230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.