


RM 500

500/70 R 24

| | |
|---------------------|--|
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BIÇERDÖVER |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| | 167 A8 ; 155 A8 |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94062430 | RC (IN) | 153.8 |
| SW (IN) | 19.8 | RIM REC | W 16 L |
| OD (IN) | 51.6 | RIM ALT | W 15 L |
| SLR (IN) | 22.5 | ECE | E11-106R-005989 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 |
|------------------------|------|------|------|------|------|-------|-------|
| 25 FREE ROLLING | 5050 | 5780 | 6490 | 7940 | 9140 | 10580 | 12010 |
| 25 DRIVE WHEEL | 3590 | 4100 | 4620 | 5640 | 6490 | 7520 | 8540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.