

FLOTATION 648 T



| | |
|---------------------------|---------------------------|
| TIRE SIZE | 550/45 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | COSECHADORA / COSECHADORA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 147 A8/144 B |
| LI/SS FREE ROLLING | 159 A8/156 B |

DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|----------|
| CÓDIGO USA | 94052066 | RC (IN) | 126.1 |
| SW (IN) | 21.7 | RIM REC | AG 16.00 |
| OD (IN) | 42.1 | PR | 16 |
| SLR (IN) | 18.7 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 35 | 38 | 41 |
|-----------|-------|-------|-------|
| 5 FR | 12350 | 12930 | 13500 |
| 10 FR | 11110 | 11640 | 12160 |
| 20 FR | 9880 | 10350 | 10800 |
| 25 FR | 8820 | 9240 | 9640 |
| 30 FR | 7940 | 8310 | 8820 |
| 5 DW | 8670 | 9090 | 9490 |
| 10 DW | 7800 | 8180 | 8540 |
| 20 DW | 6930 | 7270 | 7590 |
| 25 DW | 6190 | 6490 | 6780 |
| 30 DW | 5580 | 5840 | 6170 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.