


AGRIMAX V- FLECTO

TIRE SIZE	VF 520/70 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR / TRATOR DE ALTA POTENCIA
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	164 D



DIMENSÕES US STANDARD

CÓDIGO USA	94519194	RC (IN)	205.2
SW (IN)	21.1	RIM REC	DW 18 L
OD (IN)	68.9	ECE	E11-106R-0011692
SLR (IN)	30.4	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5020	5820	6620	7530	8330	9140	10030
FROM 40 TO 25	5510	6390	7270	8270	9150	10030	11020
20	5620	6530	7430	8430	9340	10240	11240
12	5730	6660	7570	8600	9520	10440	11460
5	6060	7030	8000	9090	10060	11030	12120
5 HT	5620	6520	7420	8430	9330	10230	11240
UPTO 5 CYC WITH FRONT LOADER	7715	8950	10185	11575	12810	14045	15435

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.