

# AW 702

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	143 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94009503	<b>RC (IN)</b>	97.4
<b>SW (IN)</b>	11.7	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	33.2	<b>ECE</b>	E4-106R-001881
<b>SLR (IN)</b>	14.6	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>78</b>
<b>5 FR</b>	8410
<b>15 FR</b>	7150
<b>20 FR</b>	6720
<b>25 FR</b>	6010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.