

# POWERTRAILER SR 331

<b>TIRE SIZE</b>	560/60 R 22.5
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TRAILER / IMPLEMENTS / TANKER
<b>VERSION</b>	IMPLEMENT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	169 D



## DIMENSIONS IS STANDARD

<b>OD (MM)</b>	1245	<b>RIM ALT</b>	17.00; AG18.00
<b>SLR (MM)</b>	565	<b>ECE</b>	E11-106R-0010147
<b>RC (MM)</b>	3775	<b>SRI</b>	600
<b>RIM REC</b>	AG 16.00		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.2	3.6	4	4.5	5	5.5	6
10	6785	7410	8145	8665	9185	9815	10440
25	5955	6505	7150	7605	8065	8615	9165
40	5125	5600	6155	6545	6940	7415	7890
50	4560	4985	5475	5825	6175	6595	7020
65	3770	4118	4524	4814	5104	5452	5800
70	3430	3745	4115	4380	4645	4960	5280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.