


# PL 801

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 21X8 - 9  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |  BIAS                            |
| <b>MACHINERY</b>    | ROTORSCHWADER / ERNTEMASCHINE<br>/ GABELSTAPLER / ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE /<br>GABELSTAPLER |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## ABMESSUNGEN IS STANDARD

|                |        |            |                 |
|----------------|--------|------------|-----------------|
| <b>SW (MM)</b> | 200    | <b>ECE</b> | E11-106R-003643 |
| <b>OD (MM)</b> | 535    | <b>PR</b>  | 14              |
| <b>RIM REC</b> | 6.00 E |            |                 |
| <b>RIM ALT</b> | 7.00 E |            |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR         | 9.00 |
|--------------------|------|
| 25 LOAD WHEEL      | 2535 |
| 25 STEER WHEEL     | 1950 |
| 10 OTHER VEHICLES  | 2535 |
| 25 OTHER VEHICLES  | 1950 |
| STATIC SIDE LOADER | 2945 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.