

# TR 678

<b>TIRE SIZE</b>	<b>600/65 - 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПОГРУЗОЧНО- ТРАНСПОРТНАЯ МАШИНА / ЭКСКАВАТОР / ПРИЦЕП
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 A2 ; 162 A6



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	610	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1644	<b>PR</b>	16
<b>SLR (MM)</b>	758	<b>TRA CODE</b>	LS2
<b>RC (MM)</b>	4916		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.60
30	4750
10	5300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.