


AGRIMAX RT 657

TIRE SIZE	540/65 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	149 D ; 152 A8



DIMENSIONER US STANDARD

USA CODE	94056927	RC (IN)	167.4
SW (IN)	20.9	RIM REC	W 16 L
OD (IN)	55.6	RIM ALT	W 18 L
SLR (IN)	25.3	ECE	E4-106R-000650

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	3440	4010	4520	5020	5520	5950	6590	7150
30	3620	4220	4750	5280	5800	6250	6930	7530
25	3760	4390	4940	5480	6030	6500	7210	7830
20	3970	4620	5200	5780	6350	6840	7590	8240
5 LT	4620	5380	6050	6720	7400	7970	8840	9600
5 HT	3970	4620	5200	5780	6350	6840	7590	8240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.