


AGRIMAX V- FLECTO

TIRE SIZE	VF 520/85 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / TRACTOR DE ALTA POTENCIA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	173 D



DIMENSIONES IS STANDARD

SW (MM)	535	RIM REC	DW 18 L
OD (MM)	2052	ECE	E11-106R-008662
SLR (MM)	911	SRI	975
RC (MM)	6111	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2955	3430	3900	4435	4905	5380	5915
FROM 65 TO 40	3250	3770	4290	4875	5395	5915	6500
30	3315	3845	4375	4970	5500	6030	6630
20	3380	3920	4460	5070	5610	6150	6760
10	3575	4145	4715	5360	5930	6505	7150
UPTO 10 CYC WITH FRONT LOADER	4550	5278	6006	6825	7553	8281	9100
10 HT	3315	3845	4375	4970	5500	6030	6630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.