


AW 711

| | |
|---------------------|--|
| TYRE SIZE | 395/55 R 16.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HAY HARVESTER / IMPLEMENT MACHINERY / IMPLEMENTS |
| VERSION | STUBBLE RESISTANT |
| TYRE TYPE | TL |
| LI/SS | 152 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 394 | RIM REC | 12 |
| OD (MM) | 838 | ECE | E11-106R-002997 |
| SLR (MM) | 365 | SRI | 400 |
| RC (MM) | 2516 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1065 | 1385 | 1705 | 1955 | 2275 | 2595 | 2770 | 3055 | 3340 | 3550 |
| 40 | 1065 | 1385 | 1705 | 1955 | 2275 | 2595 | 2770 | 3055 | 3340 | 3550 |
| 30 | 1195 | 1555 | 1915 | 2190 | 2550 | 2910 | 3105 | 3425 | 3745 | 3980 |
| 25 | 1270 | 1650 | 2030 | 2325 | 2705 | 3085 | 3300 | 3635 | 3975 | 4225 |
| 20 | 1345 | 1750 | 2150 | 2465 | 2865 | 3270 | 3495 | 3850 | 4210 | 4475 |
| 10 | 1495 | 1940 | 2390 | 2735 | 3185 | 3630 | 3880 | 4275 | 4675 | 4970 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.