


# TR 387

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>18.4 - 26</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | REMORQUE / OUTILLAGE AGRICOLE /<br>COMPACTEUR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 142 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94005000 | <b>RC (IN)</b> | 163.4          |
| <b>SW (IN)</b>  | 19.1     | <b>RIM REC</b> | DW 16 L        |
| <b>OD (IN)</b>  | 57.1     | <b>RIM ALT</b> | DW 15 L        |
| <b>SLR (IN)</b> | 25.0     | <b>ECE</b>     | E4-106R-002718 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>32</b> |
| 25               | 5840      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.