


# AW 711

<b>TIRE SIZE</b>	<b>VF 480/45 R 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94051434	<b>RC (IN)</b>	104.1
<b>SW (IN)</b>	19.3	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	34.1	<b>ECE</b>	E4-106R-002652
<b>SLR (IN)</b>	14.3		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73
<b>FROM 5 TO 30 MPH</b>	3490	4450	5410	6130	7100	8060	8900	9730	10700	12010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.