

# AW 702

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>13.0/55 - 16</b>  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | BALER / IMPLEMENT MACHINERY /<br>TRAILER / HARVESTER / IMPLEMENTS<br>/ TRAILER |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 133 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 336  | <b>RIM REC</b> | 11.0           |
| <b>OD (MM)</b>  | 770  | <b>ECE</b>     | E4-106R-002751 |
| <b>SLR (MM)</b> | 345  | <b>PR</b>      | 14             |
| <b>RC (MM)</b>  | 2256 |                |                |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.20</b> |
| <b>10 FR</b>      | 2885        |
| <b>25 FR</b>      | 2450        |
| <b>30 FR</b>      | 2305        |
| <b>40 FR</b>      | 2060        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.