

# EARTHMAX SR 475

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 18.00 R 33                                                                               |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | DUMPER RÍGIDO                                                                            |
| VERSÃO       | CUT RESISTANT COMPOUND                                                                   |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 195 B                                                                                    |



## DIMENSÕES US STANDARD

|            |          |             |           |
|------------|----------|-------------|-----------|
| CÓDIGO USA | 94064854 | RIM REC     | 13.00/2.5 |
| OD (IN)    | 73.2     | TRA CODE    | E4        |
| SLR (IN)   | 33.9     | STAR RATING | ★★★       |
| RC (IN)    | 225.2    |             |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 105   | 109   | 112   | 116   |
|-----------|-------|-------|-------|-------|
| 30        | 24700 | 25400 | 26000 | 26800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.