


# AGRIMAX RT 765M

<b>TIRE SIZE</b>	<b>710/70 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D ; 176 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94066452	<b>RC (IN)</b>	243.1
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	81.1	<b>RIM ALT</b>	DW 25 B
<b>SLR (IN)</b>	36.3	<b>ECE</b>	E11-106R-006018

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>40</b>	6730	7740	8880	10030	11180	12320	13470	14330
<b>30</b>	7080	8130	9340	10540	11740	12940	14150	15050
<b>25</b>	7390	8480	9730	10990	12250	13500	14760	15700
<b>15</b>	7750	8910	10220	11540	12860	14170	15500	16480
<b>5 LT</b>	9030	10370	11920	13450	14980	16520	18050	19200
<b>5 HT</b>	7750	8910	10220	11540	12860	14170	15500	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.