


FLOTATION 648

TIRE SIZE	700/40 - 22.5
UM	IS STANDARD
CONSTRUCTION	 BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	160 A8/156 B
LI/SS FREE ROLLING	173 A8/169 B



DIMENSIONES IS STANDARD

SW (MM)	700	RIM REC	AG 24.00
OD (MM)	1170	ECE	E4-106R-002281
SLR (MM)	510	PR	18
RC (MM)	3537		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80	3.00	3.20
10 FR	8415	8765	9100
20 FR	7575	7890	8190
30 FR	6730	7010	7280
40 FR	6010	6260	6500
50 FR	5410	5635	5800
10 DW	5825	6070	6300
20 DW	5240	5460	5670
30 DW	4660	4855	5040
40 DW	4160	4335	4500
50 DW	3745	3900	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.