

# AW 702

<b>TIRE SIZE</b>	<b>10.5/65 - 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE
<b>VERSÃO</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	130 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	270	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	760	<b>RIM ALT</b>	W 8; W 8 L
<b>SLR (MM)</b>	343	<b>ECE</b>	E11-106R-004247
<b>RC (MM)</b>	2112	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>5.30</b>
10 FR	2660
25 FR	2260
30 FR	2130
40 FR	1900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.