

AGRIMAX RT 765

TIRE SIZE	520/70 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	148 D



РАЗМЕРЫ US STANDARD

USA CODE	94063079	RC (IN)	194.0
SW (IN)	20.3	RIM REC	W 16 L
OD (IN)	64.6	RIM ALT	W 15 L; W 18 L
SLR (IN)	29.1	ECE	E11-106R-005831

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	3820	4450	5070	5700	6330	6940
30	4020	4670	5330	5990	6920	7300
25	4190	4870	5560	6240	6920	7610
20	4400	5110	5840	6560	7270	7990
5 LT	5130	5960	6800	7640	8480	9310
5 HT	4400	5110	5840	6560	7270	7990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.