

# BK-LOADER 53

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 405/70 R 18                                                                              |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | LOADER                                                                                   |
| VERSION      | ARAMID BELTED                                                                            |
| TL/TT        | TL                                                                                       |
| LI/SS        | 153A2/149A4                                                                              |



## DIMENSIONS US STANDARD

|          |          |         |                         |
|----------|----------|---------|-------------------------|
| USA CODE | 94069705 | RC (IN) | 0                       |
| SW (IN)  | 16.0     | RIM REC | 13                      |
| OD (IN)  | 41.1     | RIM ALT | 14 ; 13 SDC; 12 ;12 SDC |
| SLR (IN) | 0        |         |                         |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 22   | 29   | 36   | 44   | 51   | 58   | 65    | 73    | 80    |
|-----------|------|------|------|------|------|------|-------|-------|-------|
| 12        | 2520 | 3230 | 3810 | 4380 | 5020 | 5530 | 6100  | 6600  | 7170  |
| 5         | 2830 | 3630 | 4270 | 4920 | 5640 | 6210 | 6850  | 7410  | 8050  |
| STATIC    | 4520 | 5810 | 6850 | 7880 | 9030 | 9940 | 10970 | 11880 | 12900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.