


# AT 621

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 400/70 - 20  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | KOMPAKTLADER / BAGGERLADER /<br>BAGGERLADER / RADLADER                                 |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 B ; 168 A2   |



## ABMESSUNGEN US STANDARD

|                 |          |                |                    |
|-----------------|----------|----------------|--------------------|
| <b>USA-CODE</b> | 94060658 | <b>RC (IN)</b> | 128.8              |
| <b>SW (IN)</b>  | 15.9     | <b>RIM REC</b> | 13                 |
| <b>OD (IN)</b>  | 42.9     | <b>RIM ALT</b> | 12 SDC; 13 SDC; 14 |
| <b>SLR (IN)</b> | 19.4     | <b>PR</b>      | 16                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58   | 73    |
|-----------|------|-------|
| 30        | 7825 | -     |
| 5         | -    | 12345 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.