


EARTHMAX SR 22



| | |
|---------------------|--|
| TIRE SIZE | 20.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PLANIERER / RADLADER / PLANIERER / RADLADER / PLANIERER / PLANIERER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 177 B ; 193 A2 |

ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-----------|
| OD (MM) | 1490 | RIM ALT | 17.00/1.7 |
| SLR (MM) | 640 | TRA CODE | E2/L2 |
| RC (MM) | 4315 | STAR RATING | ★★ |
| RIM REC | 17.00/2.0 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 |
|------------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 50 | 5800 | 6150 | 6500 | 6700 | 6900 | 7300 | - | - | - | - | - |
| 10 | - | - | - | - | - | 9750 | 10000 | 10300 | 10900 | 11200 | 11500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.