


EARTHMAX SR 23

| | |
|---------------------|--|
| | 15.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | GREYDER / YÜKLEYICI |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| | 146 A8 ; 169 A2 |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| USA CODE | 94046829 | RIM REC | 12.00/1.3 |
| OD (IN) | 49.8 | TRA CODE | G2/L2 |
| SLR (IN) | 22.0 | STAR RATING | ★ |
| RC (IN) | 147.9 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 |
|-----------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 25 | 3420 | 3860 | 4400 | 4800 | 5200 | 5680 | 6150 | 6600 | - | - | - | - | - |
| 5 | - | - | - | - | - | - | - | - | 11000 | 11400 | 12000 | 12300 | 12800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.