DATA SHEET

PRINTED ON
23-04-2026

MULTIMAX MP 527

TIRE SIZE	**360/70 R 18 IND**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	PALA COMPATTA / SOLLEVATORE TELESCOPICO / PALA COMPATTA / SOLLEVATORE TELESCOPICO
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	142 A8/B

DIMENSIONI IS STANDARD

SW (MM)	360	**RIM REC**	11
OD (MM)	969	**RIM ALT**	W10; 11 SDC; W11; 12; 12 SDC
SLR (MM)	439	**ECE**	E11-106R-002996
RC (MM)	2887	**SRI**	475

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1275	1515	1725	1965	2200	2360	2650	-	-
40	1275	1515	1725	1965	2200	2360	2650	-	-
30	1365	1620	1850	2105	2360	2530	2840	-	-
25	1415	1680	1915	2180	2445	2625	2945	-	-
10 CYC.	1555	1910	2250	2585	2945	3200	3620	3820	3975
STATIC	2380	2930	3445	3965	4515	4910	5550	5855	6095

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..