

EARTHMAX SR 412



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 412

EARTHMAX SR 412 (E-4/L-4) is an All Steel radial tyre specially designed for Articulated Dump Trucks, Loaders and Dozers. The unique E-4 deep tread pattern ensures excellent traction and exceptional heat resistance. Thanks to its strong All Steel casing and belts, EARTHMAX SR 412 can carry heavy loads providing excellent stability as well as best resistance to snags and punctures. EARTHMAX SR 412 features a squared shoulder design that maximizes ground contact for excellent maneuverability.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 R 25	TL	E4	**	200 B	25.00/3.5	-	252	765	1865	834	5543	54	CR
	750/65 R 25 (30/65 R 25)	TL	E4	**	190 B	24.00/3.0	22.00/3.0 25.00/3.0	229	780	1602	715	4838	55	CR
	750/65 R 25 (30/65 R 25)	TL	E4/L4	**/*	190 B 202 A2	24.00/3.0	22.00/3.0 25.00/3.0	229	780	1602	715	4838	55	CR
Ø29"	800/65 R 29	TL	L4	**	215 A2	27.00/3.0	24.00/3.5 25.00/3.5	0	790	1805	825	5490	58	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES					PERFORMANCES			
								
								
B	215 kg							

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM		(mm)					
													
800/65 R 29	TL	E4/L4	**/*	198 B 208 A2	27.00/3.0	24.00/3.5 25.00/3.5	206	790	1805	825	5490	58	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES					PERFORMANCES			
								
								
B	215 kg							

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026