

# AGRIMAX RT 855

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>460/85 R 34</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> |   |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>      | STANDARD  |
| <b>TL/TT</b>        | TL  |
| <b>LI/SS</b>        | 147 A8/B  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94021772 | <b>RC (IN)</b> | 191.5           |
| <b>SW (IN)</b>  | 18.7     | <b>RIM REC</b> | W 16 L          |
| <b>OD (IN)</b>  | 64.8     | <b>RIM ALT</b> | W 14 L ; W 15 L |
| <b>SLR (IN)</b> | 28.4     | <b>ECE</b>     | E4-106R-000632  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 3740 | 4340 | 4950 | 5570 | 6170 | 6780 |
| 25        | 3740 | 4340 | 4950 | 5570 | 6170 | 6780 |
| 20        | 4000 | 4650 | 5310 | 5960 | 6610 | 7260 |
| 5 LT      | 5000 | 5820 | 6650 | 7460 | 8280 | 9090 |
| 5 HT      | 4000 | 4650 | 5310 | 5960 | 6610 | 7260 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.