


AGRIMAX SPARGO

TIRE SIZE	VF 320/90 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	165 D



DIMENSIONS IS STANDARD

SW (MM)	323	RIM REC	W 11
OD (MM)	1743	RIM ALT	W 10; DW 10; W 10 L; DW 11
SLR (MM)	810	ECE	E11-106R-0010077
RC (MM)	5316	SRI	825

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2050	2290	2575	2815	2955	3100	3195	3290	3455	3625	3765	3910	4030	4150	4265	4385	4575	4765
FROM 65 TO 40	2215	2475	2785	3040	3195	3350	3455	3555	3735	3915	4070	4255	4355	4485	4610	4740	4945	5150
30	2260	2525	2840	3105	3260	3420	3525	3630	3810	3995	4155	4310	4445	4575	4705	4835	5045	5255
20	2305	2575	2895	3165	3325	3485	3595	3700	3890	4075	4235	4400	4530	4665	4800	4935	5150	5360
10	2440	2720	3060	3345	3515	3685	3800	3910	4110	4310	4480	4650	4790	4930	5075	5215	5440	5665
UPTO 15 CYC.	3005	3355	3770	4120	4330	4540	4680	4820	5065	5305	5515	5725	5900	6075	6250	6425	6705	6980
UPTO 30 CYC.	2520	2810	3160	3455	3630	3805	3920	4040	4245	4450	4625	4800	4945	5090	5240	5385	5620	5850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.