


# FL 695

**600/55 R 26.5**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	RÖMORK / UYGULAMALI MAKINE / RÖMORK
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
	173 D



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	591	<b>RIM REC</b>	AG20.00
<b>OD (MM)</b>	1335	<b>ECE</b>	E11-106R-007937
<b>SLR (MM)</b>	620	<b>SRI</b>	625
<b>RC (MM)</b>	4090		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
65	--	--	--	2925	3380	3835	4225	4615	5070	5395	5720	6110	6500
50	--	--	--	3540	4090	4645	5115	5585	6135	6530	6925	7395	7865
40	--	2920	3625	3980	4600	5220	5750	6280	6900	7340	7780	8310	8840
30	2455	3240	4025	4420	5105	5795	6380	6970	7660	8150	8640	9230	9815
25	2570	3390	4215	4625	5345	6060	6680	7295	8015	8525	9040	9655	10270
20	2685	3540	4400	4830	5580	6330	6975	7615	8370	8905	9440	10085	10725
10	2925	3865	4800	5265	6085	6905	7605	8310	9130	9715	10300	11000	11700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.